



PRODUCT CARE & MAINTENANCE

GENERAL

- Regularly check all nuts and bolts on all components of canopy and/or tray are tight.
- Do not overload canopy and/or tray. Driving with too much weight, or uneven weight distribution, on rough corrugations especially, can cause too much stress on aluminium.
- Do not cause over-flexing of the vehicle chassis, in order to avoid the risk of flexing the canopy and/or tray beyond it's limits.

PROTECTIVE COATING

Over time with exposure to the elements, your protective coating may show signs of weathering such as loss of gloss, chalking and slight color change. A simple regular clean will minimise the effects of weathering and will remove dirt, grime and other build-up detrimental to all coatings.

The best method of cleaning is by regular washing of the coating using a solution of warm water and non-abrasive, pH neutral detergent solution. Surfaces should be thoroughly rinsed after cleaning to remove all residues. All surfaces should be cleaned using a soft cloth, sponge or a soft natural bristle brush.

Wash off any mud, sand, salt water, bird droppings etc asap, to prevent corrosion and to avoid having to use more abrasive cleaning techniques.

POLY WATER TANK

Your water tank is fabricated from high grade PE100 (HDPE) and will not corrode, rust or promote algae growth. It is 100% potable/drinking water safe. It is safe to clean/flush with warm soapy water.

HARDWARE

RUBBER SEALS

- To ensure the rubber seals do not become brittle or shrink, avoid prolonged exposure to direct sunlight.
- Keep clean and free of dust and grit.

CENTAFLEX HINGE

- To increase lifespan of hinge and eliminate the risk of membrane distortion from extreme temperature, avoid leaving canopy doors in open position in direct sunlight on hot days.
- An awning will help shade the hinge and allow the doors to remain open all day.

LOCKS & TRUNDLE DRAWER SLIDES

- Ensure your items are secured within the canopy, toolboxes & trundle drawer. The locks will not tolerate large impact force from loose objects and can cause the locking mechanism to fail or brake.
- We recommend using inox or WD40 spray to keep the lock shafts and trundle drawer slides lubricated and prevent them from ceasing up.
- Locks and drawer slides can very easily become embedded with a lot of dust and grit. Regularly clean locks and drawer slides with a clean cloth or brush.

**POP IN AND SEE US ANYTIME FOR
A COMPLIMENTARY CHECK-UP**

WARRANTY

Our products are covered by our 10yr manufacturer's warranty. For our warranty details, please refer to our Terms & Conditions of Trade that were attached to your original quote. Alternatively, email us for a copy or for more info.